

Technical drawing of a road cross-section. The drawing shows a parking area (parking) with a width of 5.00. The road surface has a 2% slope. A barrier (barierka zaporowa) is located at the edge of the parking area. The road width is 0.12. The distance from the barrier to the edge of the road is 1.23. The distance from the barrier to the ditch is 1.00. The ditch has a width of 0.40 and a depth of 0.50. The ditch is filled with humus (humusowanie gr 15 cm). The ditch has a slope of 1:2 (skarpa 1:2). The drawing is labeled with K2, 1, and 2.

8cm	warstwa ścierna z kostki betonowej
3cm	Podsypka cementowo-piaskowa
20cm	podbudowa z kruszywa łamanego stabilizowanego mechanicznie o kruszywie 0/31,5 mm
10cm	warstwa podłoża stabilizowanego cementem $R_m=1,5$ MPa
-	Istniejące zagęszczone podłoże gruntowe
41cm	Razem

25cm	obrzeże betonowe 8/25 cm
5cm	podsyпка cementowo - piaskowa 1:4
10cm	ława z betonu C12/15 z oporem
40cm	Razem

30cm	krawężnik betonowego 15/30 cm
5cm	podsyпка cementowo - piaskowa 1:4
10cm	ława z betonu C12/15 z oporem
45cm	Razem